



HORIZONTAL SELF-CONTAINED AIR CONDITIONERS

These CFD-SR series self-contained air conditioners (horizontal) are designed for commercial (i.e. supermarket, theatres, restaurants, office building) and industrial application.

FEATURES

- Heavily zinc coated galvanized steel cabinet.
- Various static pressure.
- Motor with a set of variable pitch diameter pulleys.
- Blower motors are fitted with inherent thermal protectors.
- Hermetic sealed scroll compressors.
- Permanent split capacitor condenser fan motor.
- Thermostatic expansion valve.
- High and low pressure switch.
- Filter drier.
- Factory test run and fully charged with R-22.

OPTIONAL COMPONENTS

- Room thermostat
- Under and over voltage protection
- Heat pump.
- Electric heater.
- R407c.



Model : CFD-SR

SPECIFICATIONS

MODEL	COOLING CAPACITY		AIR FLOW RATE		DIMENSIONS (mm)			NET WEIGHT (kg)
	Btu/h	KW	CFM	L/S	Height	Width	Depth	
CFD-SR 036Z	37,000	10.8	1,200	570	785	1,020	1,470	175
CFD-SR 052Z	51,000	14.95	1,600	770				180
CFD-SR 060Z	61,000	17.8	1,800	850				190
CFD-SR 077Z	77,000	22.6	2,400	1,150	943	1,020	1,670	270
CFD-SR 104Z	102,300	29.98	3,200	1,500	948	1,020	1,670	307
CFD-SR 122Z	126,200	36.99	3,900	1,830	992	1,400	2,290	504
CFD-SR 154Z	152,500	44.70	4,600	2,170				511
CFD-SR 208Z	205,700	60.28	6,400	3,000	1,302	1,890	2,260	905
CFD-SR 244Z	250,700	73.47	7,800	3,660	1,292	1,890	2,490	927
CFD-SR 307Z	304,300	89.18	9,200	4,330	1,495	1,890	2,490	972
CFD-SR 360Z	371,900	109	11,100	5,220				1,039

NOTE © COOLING CAPACITY BASED ON ENTERING AIR TEMP. 80 °F. DB/67 °F.WB, AMBIENT TEMP. 95 °F. DB SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE. (ข้อมูลทางเทคนิคมีเปลี่ยนแปลงได้โดยไม่ต้องแจ้งให้ทราบล่วงหน้า)